poly

VEXUS
FIBER™

TRANSFORM YOUR PHONE INTO A COMMUNICATIONS CONSOLE

BENEFITS

- Easy to track call activity on its 5" color LCD screen.

- More contacts at your fingertips with 22-line keys and 3 pages — up to 66 contacts per expansion module.

- Turn your Poly Edge Series phones into a cost-effective attendant solzution: works seamlessly with all E550 phones.

- Track even more calls and contacts with the ability to plug up to 2 modules

- Easy to install with plug-and-play setup and powering provided by the Poly Edge E500 Series host phone.

POLY EDGE E EXPANSION MODULE

Fantastic news for telephone attendants, administrative staff, and other phone power users: The Poly Edge E expansion module can help you reduce the number of lost customer calls, shorten transaction times, and support more accurate call routing. Super-charge your Poly Edge E500 Series phones with 22 multifunctional line keys that can be easily set up as line registrations, call appearances, speed dials, direct stations or busy lamp field keys. Setup is a plug-and-play snap, with power and signaling provided by the host phone. Screening, dispatching and monitoring calls has never been easier.

- 5" color LCD screen.

- 22-line keys and 3 pages.

- Up to 66 contacts per expansion module.

- Programmable line keys and a simple, intuitive user experience.

DATA SHEET

POLY EDGE E EXPANSION MODULE

Poly Edge E500 Series with 2 Expansion Modules

SPECIFICATIONS

DISPLAY

- 5 in color IPS LCD (480x800 pixel resolution)

FEATURE KEYS

- 22 multifunctional line keys configurable as line registrations, Enhanced Feature Keys, call appearances, contacts, speed dials, busy lamp fields
- Dual-color (red or green) illuminated LEDs for line status information
- 3-page keys for additional line appearances

COMPATIBLE POLY EDGE E PHONE MODELS

- Poly Edge E550

EXPANDABILITY

- Up to two Expansion Modules can be attached to a Poly Edge E550

FEATURE SUPPORT

- Additional line registrations
- Shared call appearance, bridged line appearance (key system emulation)
- Call transfer
- Busy lamp field
- Speed dial
- Fully programmable line appearances
- Multilingual user interface (driven from host phone) including[1] Arabic (UAE), Chinese (Traditional/Simplified), Czech, Danish, Dutch, English (Canada/US/UK), French (France/Canadian), German, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Slovenian, Spanish, and Swedish

POWER

- Provided by Poly Edge E host phone
- Host phone powering options: IEEE 802.3 (af/at) PoE or using the approved compatible external AC adapter for the host Poly Edge E400 or E500 series phone
- Powering starts automatically upon USB Type C port connection
- No additional power source is required

REGULATORY APPROVALS[2]

- FCC Part 15 (CFR 47)
- ICES-003
- CE Mark
- VCCI
- RCM
- China ROHS

SAFETY

- UL 62368-1
- CAN/CSA C22.2 No. 62368-1-14
- EN 60950-1/62368-1
- IEC 60950-1 and IEC 62368-1
- AS/NZS 60950.1/62368.1

OPERATING CONDITIONS

- Temperature: 0 to 40 degrees C (+32 to 104 degrees F)
- Relative humidity: 5% to 95%, noncondensing

STORAGE TEMPERATURE

- -40 to +70 degrees C (-40 to +160 degrees F)

POLY EDGE E EM COMES WITH:

- Poly Edge E EM console
- Poly Edge E EM desk stand
- Interconnection bracket and screws
- Setup sheet

UNIT BOX WEIGHT

- Shipping: 1.1 lb (0.5 kg)

UNIT BOX DIMENSIONS

- 9.7 x 7.0 x 2.7 in (246 x 178 x 68 mm)

MASTER CARTON QUANTITY

- Ten (10)

COUNTRY OF ORIGIN

- China

WARRANTY

- One (1) year

PART NUMBER

- 2200-87020-025

AVAILABLE ACCESSORIES

- Wall mount bracket 2200-47410-002

---

[1] Planned localizations

[2] Planned compliances

LEARN MORE

For more information on Edge Expansion Module visit www.poly.com/edge-e-expansion-module